

TAPE COMPATIBILITY: LW-PX400

STANDARD INDUSTRIAL POLYESTER TAPE - 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	Clear	1/4" (6 mm)	206BCPX †
		3/8" (9 mm)	209BCPX †
		1/2" (12 mm)	212BCPX †
		3/4" (18 mm)	218BCPX †
		1" (24 mm)	224BCPX †
	Translucent Matte (limited supply)	3/4" (18 mm)	218BTMPX
	White	1/6" (4 mm)	204BWPX
		1/4" (6 mm)	206BWPX †
		3/8" (9 mm)	209BWPX** †
		1/2" (12 mm)	212BWPX** †
		3/4" (18 mm)	218BWPX** †
		1" (24 mm)	224BWPX** †
	Yellow	1/4" (6 mm)	206BYPX †
		3/8" (9 mm)	209BYPX** †
		1/2" (12 mm)	212BYPX** †
		3/4" (18 mm)	218BYPX** †
		1" (24 mm)	224BYPX** †
	Green	1/4" (6 mm)	206BGPX †
		3/8" (9 mm)	209BGPX †
		1/2" (12 mm)	212BGPX †
		3/4" (18 mm)	218BGPX †
		1" (24 mm)	224BGPX †
	Blue	1/4" (6 mm)	206BBPX †
		3/8" (9 mm)	209BBPX †
		1/2" (12 mm)	212BBPX †
		3/4" (18 mm)	218BBPX †
		1" (24 mm)	224BBPX †
	Red	1/4" (6 mm)	206BRPX †
		3/8" (9 mm)	209BRPX †
		1/2" (12 mm)	212BRPX †
		3/4" (18 mm)	218BRPX †
		1" (24 mm)	224BRPX †
Orange	1/2" (12 mm)	212BOPX	
	3/4" (18 mm)	218BOPX	
	1" (24 mm)	224BOPX	
White Removable	1/2" (12 mm)	212RAPX †	
Purple	3/4" (18 mm)	218BVPX	
Matte Silver	3/8" (9 mm)	209SMPX †	
	1/2" (12 mm)	212SMPX †	
	3/4" (18 mm)	218SMPX †	
		1" (24 mm)	224SMPX †

STANDARD INDUSTRIAL POLYESTER TAPE - 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
White	Black	1/4" (6 mm)	206WBPX †
		3/8" (9 mm)	209WBPX †
		1/2" (12 mm)	212WBPX †
		3/4" (18 mm)	218WBPX †
		1" (24 mm)	224WBPX †
	Vivid Red	1/2" (12 mm)	212WRPX
		3/4" (18 mm)	218WRPX
		1" (24 mm)	224WRPX
	Vivid Green	1/2" (12 mm)	212WGPX
		3/4" (18 mm)	218WGPX
		1" (24 mm)	224WGPX
	Vivid Blue	1/2" (12 mm)	212WLPX
		3/4" (18 mm)	218WLPX
		1" (24 mm)	224WLPX
	Clear	1/2" (12 mm)	212WCPX †
3/4" (18 mm)		218WCPX †	
1" (24 mm)		224WCPX †	
Red	White	1/2" (12 mm)	212RWPX †



* INDICATES THAT SUPPLY IS ALSO AVAILABLE IN STANDARD CARTRIDGES
 ** INDICATES THAT SUPPLY IS ALSO AVAILABLE IN BULK ROLL (BULK ONLY COMPATIBLE WITH Z PRINTERS)
 † INDICATES THAT SUPPLY HAS SPLIT-BACK LINING

FLUORESCENT POLYESTER TAPE - 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	Fluorescent Red	3/4" (18 mm)	218FRPX
	Fluorescent Pink		218FPPX
	Fluorescent Orange		218FOPX †
	Fluorescent Yellow		218FYPX †
	Fluorescent Green		218FGPX †

STRONG ADHESIVE POLYESTER TAPE - 30 ft (9 m)			
Black	White	3/8" (9 mm)	209IBWPX †
		1/2" (12 mm)	212IBWPX †
		3/4" (18 mm)	218IBWPX †
		1" (24 mm)	224IBWPX †
	Yellow	3/8" (9 mm)	209IBYPX †
		1/2" (12 mm)	212IBYPX †
		3/4" (18 mm)	218IBYPX †
		1" (24 mm)	224IBYPX †
Gold	Clear	1/2" (12 mm)	212GCPX †
	Black	1/2" (12 mm)	212GBPX

VINYL TAPE - 22.9 ft (7 m)			
Black	White	1/2" (12 mm)	212VTBWPX**
		3/4" (18 mm)	218VTBWPX**
		1" (24 mm)	224VTBWPX**
	Yellow	1/2" (12 mm)	212VTBYPX**
		3/4" (18 mm)	218VTBYPX**
		1" (24 mm)	224VTBYPX**

VINYL SELF-LAMINATING OVERWRAP - 26.2 ft (8 m)			
Black	White	1" (24 mm), 1/4" White, 3/4" Clear Tail (26ft/L)	224VSLPX** †

Wire wrap tape prints on white area and has a clear tail to overlap printed material.

EXTRA TOUGH NYLON TAPE - 19 ft (5.8 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	White	1/2" (12 mm)	212NYLBWPX †
		3/4" (18 mm)	218NYLBWPX †
		1" (24 mm)	224NYLBWPX †

It is recommended to cut nylon tape using scissors to prolong the life of your printer's built-in cutter.

MAGNETIC TAPE - 4.9 ft (1.5 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	White	1/2" (12 mm)	212MTBWPX-4.9
		3/4" (18 mm)	218MTBWPX-4.9
		1" (24 mm)	224MTBWPX-4.9
	Yellow	1/2" (12 mm)	212MTBYPX-4.9
		3/4" (18 mm)	218MTBYPX-4.9
		1" (24 mm)	224MTBYPX-4.9
	Red	1/2" (12 mm)	212MTBRPX-4.9
		3/4" (18 mm)	218MTBRPX-4.9
		1" (24 mm)	224MTBRPX-4.9
	Blue	1/2" (12 mm)	212MTBBPX-4.9
		3/4" (18 mm)	218MTBBPX-4.9
		1" (24 mm)	224MTBBPX-4.9
	Green	1/2" (12 mm)	212MTBGPX-4.9
		3/4" (18 mm)	218MTBGPX-4.9
		1" (24 mm)	224MTBGPX-4.9

It is recommended to cut magnetic tape using scissors to prolong the life of your printer's built-in cutter.

HEAT SHRINK TUBE - 98 in (2.4 m)						
IMPRINT	TAPE	NOMINAL DIAMETER	AWG	SHRINK RATIO	PART NUMBER	
Black	Red	3/16" (4 mm)	8-12	2:1	205STBRPX	
		1/2" (12 mm)	2-8	2:1	211STBRPX	
	Yellow	1/8" (3 mm)	14-22	3:1	203B20BYPX**	
		3/16" (4 mm)	8-12	2:1	205STBYPX	
		1/4" (6 mm)	6-18	3:1	208B20BYPX**	
		1/2" (12 mm)	2-8	2:1	211STBYPX	
	White	1/8" (3 mm)	14-22	3:1	203B20BWPX**	
		3/16" (4 mm)	8-12	2:1	205STBWPX	
		1/4" (6 mm)	6-18	3:1	208B20BWPX**	
		3/8" (9 mm) 90in/L	4-12	3:1	210STBWPX-90	
		1/2" (12 mm)	2-8	2:1	211STBWPX	
		9/16" (14 mm)	0-5	2:1	214STBWPX	
		Blue	3/16" (4 mm)	10-18	3:1	205YLBWPX
		White	Black	3/16" (4 mm)	8-12	2:1
	1/2" (12 mm)			2-8	2:1	211STWBPX

Compliance Standards: UL Standard 224 (Related Temperature: 125° C, Rated Voltage: 300V, Flame Resistance Grade VW-1). It is recommended to cut heat shrink tube using scissors to prolong the life of your printer's built-in cutter.