

TAPE COMPATIBILITY: LW-PX900

STANDARD INDUSTRIAL POLYESTER TAPE - 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	Clear	1/4" (6 mm)	206BCPX †
		3/8" (9 mm)	209BCPX †
		1/2" (12 mm)	212BCPX †
		3/4" (18 mm)	218BCPX †
		1" (24 mm)	224BCPX †
		1 1/2" (36 mm)	236BCPX †
	Translucent Matte (limited supply)	3/4" (18 mm)	218BTMPX
	White	1/6" (4 mm)	204BWPX
		1/4" (6 mm)	206BWPX †
		3/8" (9 mm)	209BWPX**†
		1/2" (12 mm)	212BWPX**†
		3/4" (18 mm)	218BWPX**†
		1" (24 mm)	224BWPX**†
		1 1/2" (36 mm)	236BWPX**†
	Yellow	1/4" (6 mm)	206BYPX †
		3/8" (9 mm)	209BYPX**†
		1/2" (12 mm)	212BYPX**†
		3/4" (18 mm)	218BYPX**†
		1" (24 mm)	224BYPX**†
	Green	1 1/2" (36 mm)	236BYPX**†
		1/4" (6 mm)	206BGPX †
		3/8" (9 mm)	209BGPX †
		1/2" (12 mm)	212BGPX †
		3/4" (18 mm)	218BGPX †
	Blue	1" (24 mm)	224BGPX †
		1 1/2" (36 mm)	236BGPX †
		1/4" (6 mm)	206BBPX †
		3/8" (9 mm)	209BBPX †
		1/2" (12 mm)	212BBPX †
	Red	3/4" (18 mm)	218BBPX †
		1" (24 mm)	224BBPX †
		1 1/2" (36 mm)	236BBPX †
		1/4" (6 mm)	206BRPX †
		3/8" (9 mm)	209BRPX †
	Orange	1/2" (12 mm)	212BRPX †
		3/4" (18 mm)	218BRPX †
		1" (24 mm)	224BRPX †
		1 1/2" (36 mm)	236BRPX †
	Orange	1/2" (12 mm)	212BOPX
		3/4" (18 mm)	218BOPX
		1" (24 mm)	224BOPX
	Orange	1 1/2" (36 mm)	236BOPX
	White Removable	1/2" (12 mm)	212RAPX †
		3/4" (18 mm)	218RAPX †
	Matte Silver	3/8" (9 mm)	209SMPX †
		1/2" (12 mm)	212SMPX †
		3/4" (18 mm)	218SMPX †
		1" (24 mm)	224SMPX †
		1 1/2" (36 mm)	236SMPX †

STANDARD INDUSTRIAL POLYESTER TAPE - 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
White	Black	1/4" (6 mm)	206WBPX †
		3/8" (9 mm)	209WBPX †
		1/2" (12 mm)	212WBPX †
		3/4" (18 mm)	218WBPX †
		1" (24 mm)	224WBPX †
		1 1/2" (36 mm)	236WBPX †
	Vivid Red	1/2" (12 mm)	212WRPX
		3/4" (18 mm)	218WRPX
		1" (24 mm)	224WRPX
	Vivid Green	1 1/2" (36 mm)	236WRPX
		1/2" (12 mm)	212WGPX
		3/4" (18 mm)	218WGPX
	Vivid Blue	1" (24 mm)	224WGPX
		1/2" (12 mm)	212WLPX
		3/4" (18 mm)	218WLPX
		1" (24 mm)	224WLPX
	Clear	1 1/2" (36 mm)	236WLPX
		1/2" (12 mm)	212WCPX †
		3/4" (18 mm)	218WCPX †
Red	White	1" (24 mm)	224WCPX †
		1/2" (12 mm)	212RWPX †



* INDICATES THAT SUPPLY IS ALSO AVAILABLE IN STANDARD CARTRIDGES

** INDICATES THAT SUPPLY IS ALSO AVAILABLE IN BULK ROLL (BULK ONLY COMPATIBLE WITH Z PRINTERS)

† INDICATES THAT SUPPLY HAS SPLIT-BACK LINING

STRONG ADHESIVE POLYESTER TAPE- 30 ft (9 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	White	3/8" (9 mm)	209IBWPX †
		1/2" (12 mm)	212IBWPX †
		3/4" (18 mm)	218IBWPX †
		1" (24 mm)	224IBWPX †
		1 1/2" (36 mm)	236IBWPX †
	Yellow	3/8" (9 mm)	209IBYPX †
		1/2" (12 mm)	212IBYPX †
		3/4" (18 mm)	218IBYPX †
		1" (24 mm)	224IBYPX †
		1 1/2" (36 mm)	236IBYPX †
Gold	Clear	1/2" (12 mm)	212GCPX †
	Black	1/2" (12 mm)	212GBPX
FLUORESCENT POLYESTER TAPE- 30 ft (9 m)			
Black	Fluorescent Red	3/4" (18 mm)	218FRPX
	Fluorescent Pink		218FPPX
	Fluorescent Orange		218FOPX †
	Fluorescent Yellow		218FYPX †
	Fluorescent Green		218FGPX †
VINYL TAPE - 22.9 ft (7 m)			
Black	White	1/2" (12 mm)	212VTBWPX**
		3/4" (18 mm)	218VTBWPX**
		1" (24 mm)	224VTBWPX**
		1 1/2" (36 mm)	236VTBWPX**
	Yellow	1/2" (12 mm)	212VTBYPX**
		3/4" (18 mm)	218VTBYPX**
		1" (24 mm)	224VTBYPX**
		1 1/2" (36 mm)	236VTBYPX**
VINYL SELF-LAMINATING OVERWRAP - 26.2 ft (8 m)			
Black	White	1" (24 mm), 1/4" White, 3/4" Clear Tail (26ft/L)	224VSLPX**†
		1 1/2" (36 mm), 1/2" White, 1" Clear Tail (26ft/L)	236VSLPX**†

Wire wrap tape prints on white area and has a clear tail to overlap printed material.

EXTRA TOUGH NYLON TAPE - 19 ft (5.8 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	White	1/2" (12 mm)	212NYLBWPX †
		3/4" (18 mm)	218NYLBWPX †
		1" (24 mm)	224NYLBWPX †

It is recommended to cut nylon tape using scissors to prolong the life of your printer's built-in cutter.

MAGNETIC TAPE - 4.9 ft (1.5 m)			
IMPRINT	TAPE	WIDTH	PART NUMBER
Black	White	1/2" (12 mm)	212MTBWPX-4.9
		3/4" (18 mm)	218MTBWPX-4.9
		1" (24 mm)	224MTBWPX-4.9
		1 1/2" (36 mm)	236MTBWPX-4.9
	Yellow	1/2" (12 mm)	212MTBYPX-4.9
		3/4" (18 mm)	218MTBYPX-4.9
		1" (24 mm)	224MTBYPX-4.9
		1 1/2" (36 mm)	236MTBYPX-4.9
	Red	1/2" (12 mm)	212MTBRPX-4.9
		3/4" (18 mm)	218MTBRPX-4.9
		1" (24 mm)	224MTBRPX-4.9
		1 1/2" (36 mm)	236MTBRPX-4.9
	Blue	1/2" (12 mm)	212MTBBPX-4.9
		3/4" (18 mm)	218MTBBPX-4.9
		1" (24 mm)	224MTBBPX-4.9
		1 1/2" (36 mm)	236MTBBPX-4.9
	Green	1/2" (12 mm)	212MTBGPX-4.9
		3/4" (18 mm)	218MTBGPX-4.9
		1" (24 mm)	224MTBGPX-4.9
		1 1/2" (36 mm)	236MTBGPX-4.9

It is recommended to cut magnetic tape using scissors to prolong the life of your printer's built-in cutter.

HEAT SHRINK TUBE - 98 in (2.4 m)					
IMPRINT	TAPE	NOMINAL DIAMETER	AWG	SHRINK RATIO	PART NUMBER
Black	Red	3/16" (4 mm)	8-12	2:1	205STBRPX
		1/2" (12 mm)	2-8	2:1	211STBRPX
	Yellow	1/8" (3 mm)	14-22	3:1	203B20BYPX**
		3/16" (4mm)	8-12	2:1	205STBYPX
		1/4" (6 mm)	6-18	3:1	208B20BYPX**
		1/2" (12 mm)	2-8	2:1	211STBYPX
		7/8" (22 mm)	0000-1	2:1	221STBYPX
	White	1/8" (3 mm)	14-22	3:1	203B20BWPX**
		3/16" (4 mm)	8-12	2:1	205STBWPX
		1/4" (6 mm)	6-18	3:1	208B20BWPX**
		3/8" (9 mm) 90in/L	4-12	3:1	210STBWPX-90
		1/2" (12 mm)	2-8	2:1	211STBWPX
		9/16" (14 mm)	0-5	2:1	214STBWPX
		7/8" (22 mm)	0000-1	2:1	221STBWPX
	Blue	3/16" (4 mm)	10-18	3:1	205YLBWPX
White	Black	3/16" (4 mm)	8-12	2:1	205STWBWPX
		1/2" (12 mm)	2-8	2:1	211STWBWPX

Compliance Standards: UL Standard 224 (Related Temperature: 125° C, Rated Voltage: 300V, Flame Resistance Grade VW-1). It is recommended to cut heat shrink tube using scissors to prolong the life of your printer's built-in cutter.